Security Constrained Optimal Power Flow for AC/DC grids



Overview

- Motivation
- > Preventive and Preventive-Corrective SCOPF models for hybrid AC/DC system
- > Test results
- > Preventive-short-term-corrective SCOPF for hybrid AC/DC grid
- > Extension to multi-period AC/DC SCOPF model
- > Future work











Motivation

- Current reliability assessment based on N-1 criterion
- Likelihood of contingencies not considered
- May lead to cases with higher operational costs or higher risk
- Increased penetration of RES, smart grids, intra-day markets → increasing uncertainties
- Equal probabilities, static list of contingencies not optimal

Shift to Probabilistic Reliability Criteria!

- Current approaches → Preventive security and Preventive-corrective security
- Preventive-corrective : opportunity for trade-off between costs of measures and system risk

Quantitative assessment of preventive measures and system risk

- Development of HVDC grids fully controllable exchange between AC and DC grids
- Flexibility from AC/DC converter (active as well as reactive power)
 - preventive measures
 - o fast corrective actions (smaller time constants)
- More economical than re-dispatch, load curtailment

Inclusion of HVDC in reliable grid operation!













Preventive SCOPF model for hybrid AC/DC grid

Objective : To minimize the preventive redispatch cost

- Decision variables:
 - Generator active power redispatch in base case
 - Converter ac side active power redispatch in base case
















Preventive-Corrective SCOPF model for hybrid AC/DC grid

- Objective: To minimize total of preventive redispatch cost and corrective risk, which is equated to probability of a contingency times the corrective redispatch cost
- Decision variables:
 - Base case
 - Generator active power redispatch,
 - Converter ac side active power redispatch
 - Contingency case
 - Generator active power redispatch
 - Converter ac side active power redispatch
 - Active power component of load shedding



$$min \sum_{g=1}^{N_g} \left| \Delta P_g^{prev} \right| . C_g^{prev} + \sum_{c=1}^{N_c} \left| \Delta P_c^{prev} \right| . C_c^{prev} + \sum_{cont=1}^{N} prob_{cont} . \left(\sum_{g=1}^{N_g} \left| \Delta P_g^{corr} \right| . C_g^{corr} + \sum_{l=1}^{N_l} \left| \Delta P_l \right| . VOLL + \sum_{c=1}^{N_c} \left| \Delta P_c^{corr} \right| . C_c^{corr} \right)$$

First stage = Preventive actions cost

Second stage = Corrective risk











P^{corr}, Q^{corr} for participating

generators, loads

Constraints - SCOPF model for hybrid AC/DC grid

- Equality constraints
 - AC grid active and reactive power flow equations
 - DC grid active power flow equations
 - Nodal balance equations (KCL) for AC and DC nodes
 - Converter station power flow equations
 - Transformer active and reactive power flows
 - Filter reactive power flow
 - Phase reactor active and reactive power flows
 - Converter power balance equations and losses

- Inequality constraints
 - Generator active power and reactive power limits
 - Load active power and reactive power limits
 - Nodal (AC and DC) voltage limits
 - AC branch thermal limits
 - DC branch flow rating limits
 - Converter ac side active power and reactive power limits, current limits
 - Converter dc side active power limits, current limits
 - For LCC configuration, firing angle limits











Implementation of AC/DC SCOPF models

➤ Implementation of SCOPF (Security Constrained Optimal Power Flow) model for hybrid AC/DC grid using Julia/JuMP platform

> Built on:

- PowerModels.jl package (power system optimization toolbox developed by the Los Alamos National Lab)
 - https://github.com/lanl-ansi/PowerModels.jl
- Extension packages PowerModelsACDC.jl
 (https://github.com/hakanergun/PowerModelsACDC.jl) and PowerModelsReliability.jl
 (https://github.com/frederikgeth/PowerModelsReliability.jl)














Test Results

67 bus system - Impact of contingency probability on preventive-corrective redispatch

- ➤ 67 AC bus AC/HVDC Overlay system
- ➤ 17 synchronous generation units and 3 wind farms
- ➤ 9 Voltage Source Converters (VSCs)
- CostCorr/CostPrev = 10 for generators and VSCs
- > 102 AC lines and 11 DC lines
- ➤ 13 critical contingencies realized







(a) AC grid topology

(b) DC grid topology

Source: Sass, F., Sennewald, T., Marten, A., Westermann, D., "Mixed AC high-voltage direct current benchmark test system for security constrained optimal power flow calculation", IET Gener. Transm. Distrib., 2017









Test Results

67 bus system – Comparison of preventive and preventive-corrective security

offshore

- > Tripping of AC branch 2-12 considered (probability = 0,005)
- CostCorr/CostPrev = 10 for generators and VSCs

Preventive-Corrective AC/DC SCOPF


Converters participate in preventive and corrective stages


	Total Risk (€/h)	First stage/Preventive cost (€/h)		Sec	Second stage/Corrective risk (€/h)		
I	7,89	0			7,89		
	Preventive Generator Redispatch (MW)		Preventive Conver Redispatch (MW)	ter	Corrective Generator Redispatch (MW)	Corrective Converter Redispatch (MW)	
	0		0		9,93	58,6	

Converters participate in preventive stage only

Total Risk (€/h)	First stage/Preventive cost (€/h)		Second stage/Corrective risk (€/h)			
12,615	0,0336			12,581		
Preventive Generator Redispatch (MW)		Preventive Conver Redispatch (MW)	ter	Corrective Generator Redispatch (MW)	Corrective Converter Redispatch (MW)	
0,00)338	0		25,2	-	







(a) AC grid topology

Source: Sass, F., Sennewald, T., Marten, A., Westermann, D., "Mixed AC high-voltage direct current mark test system for security constrained optimal power flow calculation". IET Gener, Transm. Distrib

benchmark test system for security constrained optimal power flow calculation", IET Gener Transm. Distrib., 2017







(b) DC grid topology





Test Results

67 bus system – Comparison of preventive and preventive-corrective security

- > Tripping of AC branch 2-12 considered (probability = 0,005)
- CostCorr/CostPrev = 10 for generators and VSCs

Preventive-Corrective AC/DC SCOPF

Converters participate in preventive and corrective stages

Total Risk (€/h)	First sta	rst stage/Preventive cost (€/h)		Second stage/Corrective risk (€/h)		
7,89		Preventive Converte		7,89		
Preven Genera Redispa (MW	itor itch			Corrective Generator Redispatch (MW)	Corrective Converter Redispatch (MW)	
0		0		9,93	58,6	

Converters participate in preventive stage only

					•	
Total Risk (€/h)	First stage/Preventive cost (€/h)		Second stage/Corrective risk (€/h)			
12,615	0,0336			12,581		
Preventive Generator Redispatch (MW)		Preventive Conver Redispatch (MW)	ter	Corrective Generator Redispatch (MW)	Corrective Converter Redispatch (MW)	
0,00)338	0		25,2	-	

Preventive AC/DC SCOPF

Preventive cost (€/h)			
355,53			
Preventive Generator Redispatch (MW)	Preventive Converter Redispatch (MW)		
32,39	31,6		












Current work

Preventive-short-term-corrective SCOPF for hybrid AC/DC grid

- Implementation explicitly considering delays of different control actions
- ➤ Evaluate flexibility offered by fast dynamics of AC/DC converters
- Capture fast control response of AC/DC converters in short-term (ST) stage
- ➤ Slower generator redispatch as corrective stage
- ➤ Preventive SCOPF as reference problem to assess impact of different stages of control



Preventive-short-term-corrective SCOPF model (single time instant) for AC/DC system












Extension to multi-period AC/DC SCOPF model













Future work

- Analysis for multi-period AC/DC SCOPF model based on test cases
- Comparison between the single time instant and multi-period models for resulting costs and risk











Thank you!

Vaishally Bhardwaj

vaishally.bhardwaj@kuleuven.be

"Uncertainty is a very good thing: it's the beginning of an investigation, and the investigation should never end." Tim Crouch

https://innodc.org/



https://twitter.com/Inno_DC



https://www.linkedin.com/in/innodc-innovative-tools-for-offshore-wind-and-dc-grids-728138166/









